

## EQUIPMENT SPEC SHEET



<u>Dimensions &amp; Spec</u>	<u>SNLU</u>
Outside Length	53'
Inside Length	631"
Inside Width	100.375"
Inside Height	109.5"
Cube Capacity	4,014 '
Height under Castings (Distance)	105.875" (90.375")
<b>Scaleable Weight</b>	<b>43,500</b>

<u>Dimensions &amp; Spec</u>	<u>SNLU3</u>
Outside Length	53'
Inside Length	630.5"
Inside Width	99"
Inside Height	109"
Cube Capacity	3,955 '
Height under Castings (Distance)	105" (84.25)
<b>Scaleable Weight</b>	<b>43,500</b>

<u>Dimensions &amp; Spec</u>	<u>Trailer</u>
Outside Length	53'
Inside Length	629.3"
Inside Width	100.75"
Inside Height	110"
Cube Capacity	4,090 '
Between Castings (Height) -	
<b>Scaleable Weight</b>	<b>45,000</b>

### Examples of Scaleable Weight by Tractor Type

<u>Tractor Type</u>	<u>SNLU</u>	<u>SNLU3</u>	<u>53' Trailer</u>
Daycab (Avg. 15,500)	45,500	45,500	45,500
Regional (Avg. 17,840)	43,500	43,500	45,500
OTR (Avg. 18,780)	42,500	42,500	45,500

\*\* 43,500 is the maximum scaleable weight to the customer. Any increase over that weight must be approved in conjunction with the Intermodal Regional Director of Operations because of variances in box types and weights, chassis weights, and tractor capacity and weights.\*\*

